



VersaPatch® Latex Modified Floor Patch and Leveler

1. PRODUCT NAME

TEC® VersaPatch® Latex Modified Floor Patch and Leveler (TA-327) 

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
800.552.6225 Office
800.952.2368 Fax
tecspecialty.com

3. DESCRIPTION

VersaPatch® Latex Modified Floor Patch and Leveler is a fast setting cement-based product designed specifically for patching and filling cracks, voids, seams and depressions in most floor surfaces from featheredge up to 1/2" (12 mm) deep. Flat trowel to produce a smooth, level, non-cracking surface. The resulting finish is ideal for the installation of sheetgoods, resilient tile, carpet, wood and ceramic or stone tile.

Key Features and Benefits

- Patch 1/2" (12 mm) down to a featheredge
- Fast setting—install flooring in 30 to 45 minutes
- Latex modified smooth surface patch
- Use on wood, concrete and most other existing flooring materials
- Self-drying formula

Packaging

25 lb. plastic bags (11.34 kg)	Product #7155813011
25 lb. moisture-resistant bags (11.34 kg)	Product #7155813017
9.75 lb. Pure Pak* container (4.42 kg)	Product #7155815311

*Registered trademark of Excello Corporation

Coverage

Coverages shown are approximate. Actual coverages may vary according to substrate conditions and thickness of applications.

Application Depth	Approximate Coverage	
	per 25 lbs. (11.34 kg)	per 9.75 lbs. (4.42 kg)
1/8" (3 mm)	26-29 sq.ft. (2.4-2.7 m ²)	10-11.5 sq.ft. (0.9-1.7 m ²)
1/4" (6 mm)	13-14 sq.ft. (1.2-1.3 m ²)	5-5.5 sq.ft. (0.5 m ²)
1/2" (12 mm)	6-7 sq.ft. (0.6-0.7 m ²)	2.5-2.75 sq.ft. (0.2-0.3 m ²)

Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete
- Cement backerboards
- Concrete terrazzo
- Ceramic tile, pavers, brick
- Quarry tile
- Exterior grade plywood, C-C (plugged) or better
- Exterior Grade Lauan Plywood—Type I Trademarked Exterior Grade, OVL, CC, BB, OVL face grades only (Note: Lauan plywood is an unacceptable substrate for the installation of resilient, ceramic or marble tile)
- Vinyl composition tile (VCT), embossed resilient floor coverings must be single layer and well bonded to an approved substrate*
- Adhesive residue (except for tacky or pressure sensitive adhesive)*
- Gypsum substrates**—minimum tensile bond strength 72 psi (0.5 MPa)

* Requires mixing with TEC® Patch Additive or, in lieu of the additive, prime substrate with TEC® Multipurpose Primer.

** Requires priming with TEC® Multipurpose Primer.

Substrate Preparation

All surfaces must be structurally sound, dry and free from oil, grease, dust, loose or peeling paint, sealers, floor finishes, curing compounds or any contaminant that would prevent a good bond. Concrete and cementitious substrates must be fully cured and free of any hydrostatic pressure or excessive moisture [15 lb. per 1000 ft² (0.07 kg/m²) per 24 hours, RH 95% or lower]. All surface protrusions must be removed by sanding, scraping or chipping. Remove all dust by vacuuming. Not recommended for use over expansion or control joints.

Notes: Vinyl asbestos tile or any substrate containing asbestos must not be sanded, scored or scarified because of the potential health hazard of breathing dust. Any substrate containing asbestos must be handled in accordance with existing EPA regulations. Contact your local EPA office.

Storage

Store in a cool, dry area away from direct sunlight. Do not store open containers.

Shelf Life

Maximum shelf life is from date of manufacture in unopened package.
Plastic bag: 3 years Moisture-resistant bag: 1 year Pure Pak: 1 year

Limitations

- Only for interior use.
- Do not use where there is hydrostatic pressure or excessive moisture conditions.
- Not for use as a wear surface or to patch over gypsum surfaces, sealed concrete, epoxy terrazzo, tempered hardboard, particle board, strip wood flooring, over heavily cushioned flooring or perimeter bonded flooring.
- Do not apply when the temperature is below 50°F (10°C).

Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered TEC® brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

Physical Properties

VersaPatch® Latex Modified Floor Patch and Leveler (TA-327)	
Description	
Physical State	Dry powder
Color	Gray
Pot Life	10-15 minutes
Install Floor Covering*	30-45 minutes
Storage	Store in cool, dry location. Do not expose to nor store in direct sunlight. Do not store open containers.
Shelf Life	Maximum shelf life is from date of manufacture in properly stored, unopened package. Plastic bag: 3 years Moisture-resistant bag: 1 year Pure Pak: 1 year

*Flooring installation after application is dependent on thickness, drying conditions, and type of flooring.

5. INSTALLATION INSTRUCTIONS

Mixing

For best results, VersaPatch® Latex Modified Floor Patch and Leveler and room should be at 50°F to 70°F (10°-21°C) for 24 hours before, during and 48 hours after installation. In a clean mixing container, add product to clean, cool, water as specified in the chart.

Size	Water
25 lbs. (11.34 kg)	3 to 4 quarts (2.8 to 3.8 L)
9.75 lbs. (4.42 kg)	4¾ to 6⅓ cups (1.12 to 1.5 L)

Add powder to liquid for ease of mixing. Mix thoroughly to a smooth, lump-free consistency. For smaller amounts use a ratio of 3 parts powder to 1 part water. Avoid breathing dust and contact with eyes and skin. Avoid using high speed mixing—not to exceed 300 rpm. Mix only as much patching compound as can be used in 10 to 15 minutes. **Use immediately.**

Note: For applications where TEC® Patch Additive is required, follow detailed mixing directions on the patch additive label.

Application

Immediately after mixing, work the VersaPatch® into the void to be filled with a flat steel trowel and then finish to a level surface to the required smoothness. The working time for this product is 10 to 15 minutes depending upon the temperature. High temperature will shorten the working time. For repairs greater than ½" (12 mm) in thickness, you will need two applications, allowing the first application to set before applying the second. Do not exceed a total thickness of 1" (25 mm) of VersaPatch. Do not overwork the product.

Curing

VersaPatch® is fast drying and can accept foot traffic and the installation of most floor covering materials within 30-45 minutes. Protect from excessive heat or drafty conditions during curing period.

Clean-up

Wash tools, hands and equipment with warm soapy water while material is still fresh.

6. AVAILABILITY

TEC® Premium Tile and Stone Installation Products are available nationwide. To locate TEC® products in your area, please contact:

Phone: 800-832-9002
 Website: tecspecialty.com

7. WARRANTY

For warranty details, see your sales associate or tecspecialty.com.

8. MAINTENANCE

Not applicable

9. TECHNICAL SERVICES

Technical assistance

Information is available by calling the Technical Support Hotline.
 Toll Free: 800-832-9023
 Fax: 630-952-1235

Technical and safety literature

To acquire technical and safety literature, please visit our website at tecspecialty.com.

10. FILING SYSTEM

Division 9

